



WATER CONNECTION 3/4" GAS



DRAINING PIPE Ø 24mm



ELECTRICAL SUPPLY

TECHNICAL DATA	
EXTERNAL DIMENSIONS	
width	590 mm
depth	600 mm
height	1290 mm
WEIGHT	68.5 kg
VOLTAGE	400V 3N 50Hz
POWER REQUIRED	6900 W
WATER HARDNESS	2-8 °F
INLET WATER PRESSURE	200-400 kPa
CROCKERY DIMENSIONS	
plates diameter	380 mm
dishes max. height	355 mm
RACK DIMENSIONS	
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060
WASHING CYCLES (sec)	1 (90) 2 (180)
WATER SUPPLY 55°C	
racks/h(*) ⁽¹⁾	40 20
WATER SUPPLY 10°C	
racks/h(*) ⁽¹⁾	26 20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L
BOILER CAPACITY	5.7 L
BOILER HEATING ELEMENT	6000 W
RINSING TEMPERATURE (SET)	85°C
TANK CAPACITY	29 L
TANK HEATING ELEMENT	2700 W
TANK TEMPERATURE (SET)	55°C
PUMP POWER	900 W (500 L/min ^{***})
DRAIN PUMP (optional)	25 W h MAX drainig 0.8m (40 L/min ^{***})
NOISE	63 dB(A)

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

⁽¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.