



	WATER CONNECTION 3/4" GAS
	DRAINING Ø 24mm
	ELECTRICAL SUPPLY

(***) MIN 130-MAX 200

TECHNICAL DATA			
EXTERNAL DIMENSIONS			
width		720 mm	
depth		735 mm	
height		1445/1880(open hood) mm	
WEIGHT		100 kg	
VOLTAGE		400V 3N 50Hz	
POWER REQUIRED		10120 W	
WATER HARDNESS		2-8 °F	
INLET WATER PRESSURE		200-400 kPa	
CROCKERY DIMENSIONS			
plates diameter		410 mm	
trays max. dimension		GASTRONORM 1/1 (530x325)	
RACK DIMENSION		500X500 mm	
RACK EQUIPMENT		2XC40 - 1XC44 - 2X15060	
WASHING CYCLES	(sec)	1 (50)	2 (120)
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾		70	30
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾		34	30
WATER CONSUMPTION / CYCLE (water pressure 200kPa)		2.8 l	
BOILER CAPACITY		10 l	
BOILER HEATING ELEMENT		9000 W	
RINSING TEMPERATURE (SET)		85°C	
TANK CAPACITY		30 l	
TANK HEATING ELEMENT		2700 W	
TANK TEMPERATURE (SET)		55°C	
PUMP POWER		1120 W(630 L/min***)	
DRAIN PUMP (optional)		190 W(120 L/min***)	
NOISE		63,6±0.7 dB(A)	

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.