



| | |
|--|---------------------------|
| | WATER CONNECTION 3/4" GAS |
| | DRAINING Ø 24mm |
| | ELECTRICAL SUPPLY |

(***) MIN 130-MAX 200

| TECHNICAL DATA | | | |
|---|----------------------|--------------------------|--------|
| EXTERNAL DIMENSIONS | | | |
| width | | 720 mm | |
| depth | | 735 mm | |
| height | | 1445/1880(open hood) mm | |
| WEIGHT | | 100 kg | |
| VOLTAGE | | 400V 3N 50Hz | |
| POWER REQUIRED | | 10120 W | |
| WATER HARDNESS | | 2-8 °F | |
| INLET WATER PRESSURE | | 200-400 kPa | |
| CROCKERY DIMENSIONS | | | |
| plates diameter | | 410 mm | |
| trays max. dimension | | GASTRONORM 1/1 (530×325) | |
| RACK DIMENSION | | 500X500 mm | |
| RACK EQUIPMENT | | 2XC40 - 1XC44 - 2X15060 | |
| WASHING CYCLES (sec) | 1<50> | 2<120> | 3<180> |
| WATER SUPPLY 55°C | | | |
| racks/h(*) ⁽¹⁾ | 70 | 30 | 20 |
| WATER SUPPLY 10°C | | | |
| racks/h(*) ⁽¹⁾ | 34 | 30 | 20 |
| WATER CONSUMPTION / CYCLE (water pressure 200kPa) | 2.8 l | | |
| BOILER CAPACITY | 10 l | | |
| BOILER HEATING ELEMENT | 9000 W | | |
| RINSING TEMPERATURE (SET) | 85°C | | |
| TANK CAPACITY | 30 l | | |
| TANK HEATING ELEMENT | 2700 W | | |
| TANK TEMPERATURE (SET) | 55°C | | |
| PUMP POWER | 1120 W(630 L/min***) | | |
| DRAIN PUMP (optional) | 190 W(120 L/min***) | | |
| NOISE | 63,6±0.7 dB(A) | | |

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.