



	WATER CONNECTION 3/4" GAS
	DRAINING Ø 24mm
	ELECTRICAL SUPPLY

(***) MIN 130-MAX 200

TECHNICAL DATA			
EXTERNAL DIMENSIONS			
width		720 mm	
depth		735 mm	
height		1445/1880(open hood) mm	
WEIGHT		100 kg	
VOLTAGE		400V 3N 50Hz	
POWER REQUIRED		10120 W	
WATER HARDNESS		2-8 °F	
INLET WATER PRESSURE		200-400 kPa	
CROCKERY DIMENSIONS			
plates diameter		410 mm	
trays max. dimension		GASTRONORM 1/1 (530×325)	
RACK DIMENSION		500X500 mm	
RACK EQUIPMENT		2XC40 - 1XC44 - 2X15060	
WASHING CYCLES (sec)	1<50>	2<120>	3<180>
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾	70	30	20
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾	34	30	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.8 l		
BOILER CAPACITY	10 l		
BOILER HEATING ELEMENT	9000 W		
RINSING TEMPERATURE (SET)	85°C		
TANK CAPACITY	30 l		
TANK HEATING ELEMENT	2700 W		
TANK TEMPERATURE (SET)	55°C		
PUMP POWER	1120 W(630 L/min***)		
DRAIN PUMP (optional)	190 W(120 L/min***)		
NOISE	63,6±0.7 dB(A)		

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.