
KROMO EXCELLENCE IN DISHWASHING	LUX 85 EL PLUS				Approvato PRG	
					Emesso DOC	
Md.7.2.3.1	Rev. 01	Data. 01/02/2012			Famiglia	DW123E



	WATER CONNECTION 3/4"GAS
	DRAIN PIPE Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA				
EXTERNAL DIMENSIONS				
width	600 mm			
depth	700 mm			
height	1380 mm			
WEIGHT(basic version)	87 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	10120 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200-400 kPa			
CROCKERY DIMENSIONS				
plates diameter	450 mm			
size allowed	440 mm/EURONORM			
RACK DIMENSIONS	500X500 mm			
RACK EQUIPMENT	1XC40 - 1XC43 - 1XC44 - 1X15060			
WASHING CYCLES (sec)	1 (60)	2 (120)	3 (180)	4 (300)
WATER SUPPLY 55°C				
racks/h(*)(1)	60	30	20	12
WATER SUPPLY 10°C				
racks/h(*)(1)	33	30	20	12
WATER CONSUMPTION / CYCLE	2.6 l			
BOILER CAPACITY	15 l			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	25 l			
TANK HEATING ELEMENT	2700 W			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	1120 W (630 l/min***)			
DRAIN PUMP (optional)	190 W (120 l/min***)			
NOISE	63.8 dB(A)			

(*) STANDARD TERMOSTOP (***) MAXIMUM FLOW RATE

(1) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.

N.B. A TERMINE DI LEGGE CI RISERVIAMO LA PROPRIETA' DI QUESTO DISEGNO CON DIVIETO DI RIPRODURLO O DI RENDERLO NOTO A TERZI O A DITTE CONCORRENTI SENZA NOSTRO CONSENSO SCRITTO